

### Safety Data Sheet

Copyright,2022, Acota Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Acota products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Acota, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** QD28- HFE72DA                      **Version number:** 18.00  
**Revision date:** 23/06/2022                      **Supersedes date:** 26/06/2020

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Acota HFE 72DA Engineered Fluid

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

For Industrial Use Only. See Limitations on Use for supplemental information on intended applications including Medical Device applications.

##### Restrictions on Use

Acota Engineered Fluids are used in a wide variety of applications including but not limited to precision cleaning of medical devices and as a lubricant deposition solvent for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Acota solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration. Acota will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the Acota product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that an Acota product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of an Acota product can vary widely and affect the use and intended application of an Acota product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the Acota product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Maesbury Industrial Estate, Maes Y Clawdd, Oswestry, UK SY10 8NN  
**Email:** sales@acota.co.uk  
**Website:** www.acota.co.uk

#### 1.4. Emergency telephone number

+44 (0)1743 466200

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

This material has been tested for acute inhalation toxicity and the test results do not meet the criteria for classification.

#### CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

WARNING.

#### Symbols

GHS07 (Exclamation mark) |



#### Pictograms

#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
trans-dichloroethylene	156-60-5	205-860-2	66 - 70

#### HAZARD STATEMENTS:

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

#### Prevention:

P261A Avoid breathing vapours.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### SUPPLEMENTAL INFORMATION:

**Supplemental Hazard Statements:**

EUH018

In use, may form flammable/explosive vapour-air mixture.

**Supplemental Precautionary Statements:**

Provide ventilation adequate to maintain vapor concentration below lower explosive concentration.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients**
**3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
trans-dichloroethylene	(CAS-No.) 156-60-5 (EC-No.) 205-860-2 (REACH-No.) 01-2120093504-55	66 - 70	Flam. Liq. 2, H225 Acute Tox. 4, H332 Aquatic Chronic 3, H412 Nota C Eye Irrit. 2, H319 STOT SE 3, H336
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1-ethoxy 1,1,2,2,3,3,4,4,4-nonafluorobutane	(EC-No.) 425-340-0	10 - 30	Aquatic Chronic 4, H413 EUH018
Reaction Mass of 1,1,2,3,3,3-hexafluoro1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	(EC-No.) 422-270-2	6 - 14	Substance not classified as hazardous
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (REACH-No.) 01-2119457558-25	1 - 3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Wash with soap and water. If you feel unwell, get medical attention.

### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:  
Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

No closed-cup flash point but flam/expl. vapor air mixture Material displays no closed-cup flash point but may form flammable/explosive vapor air mixture.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Hydrogen Fluoride	During combustion.

### 5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sparks/flames/extreme heat Keep away from sparks, flames, and extreme heat. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Eliminate ignition sources when cleaning spill Eliminate all potential ignition sources when cleaning up spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic

absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Contents may be under pressure, open carefully. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products. Keep away from sparks/flames/extreme heat Keep away from sparks, flames, and extreme heat.

#### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store at temperatures not exceeding 38C/100F Store away from strong bases. Store away from oxidising agents.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4nonafluoro-butane propan-2-ol	425-340-0	Manufacturer determined	TWA(as total isomers):200 ppm(2160 mg/m <sup>3</sup> )	
	67-63-0	UK HSC	TWA:999 mg/m <sup>3</sup> (400 ppm);STEL:1250 mg/m <sup>3</sup> (500 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling **Biological limit**

##### values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Derived no effect level (DNEL)**

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
trans-dichloroethylene		Consumer	Inhalation, Long-term exposure (24 hours), Systemic effects	198 mg/m <sup>3</sup>
trans-dichloroethylene		Consumer	Oral, Long-term exposure (24 hours), Systemic effects	57 mg/kg bw/d
trans-dichloroethylene		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	797 mg/m <sup>3</sup>
propan-2-ol		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	888 mg/kg bw/d
propan-2-ol		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	500 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
trans-dichloroethylene		Agricultural soil	0.0563 mg/kg d.w.
trans-dichloroethylene		Freshwater	0.0364 mg/l
trans-dichloroethylene		Freshwater sediments	0.5483 mg/kg d.w.
trans-dichloroethylene		Grassland average	0.0563 mg/kg d.w.
trans-dichloroethylene		Intermittent releases to water	0.3636 mg/l
trans-dichloroethylene		Marine water	0.0036 mg/l
trans-dichloroethylene		Marine water sediments	0.0548 mg/kg d.w.
trans-dichloroethylene		Sewage Treatment Plant	17 mg/l
propan-2-ol		Agricultural soil	28 mg/kg d.w.
propan-2-ol		Concentration in marine fish for secondary poisoning	160 mg/kg w.w.
propan-2-ol		Freshwater	140.9 mg/l
propan-2-ol		Freshwater sediments	552 mg/kg d.w.
propan-2-ol		Intermittent releases to water	140.9 mg/l
propan-2-ol		Marine water	140.9 mg/l
propan-2-ol		Marine water sediments	552 mg/kg d.w.

propan-2-ol		Sewage Treatment Plant	2,251 mg/l
-------------	--	------------------------	------------

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from UK HSC

### 8.2. Exposure controls

In addition, refer to the annex for more information.

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide ventilation adequate to maintain vapor concentration below lower explosive concentration.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect vented goggles.

##### *Applicable Norms/Standards*

Use eye protection conforming to EN 166

##### Skin/hand protection

Chemical protective gloves are not required under normal use conditions. However, when the product is subjected to extreme heat, HF may be formed. For those cases, neoprene gloves and apron are recommended.

##### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

##### *Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter type A

#### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Liquid.
<b>Colour</b>	Colourless
<b>Odour</b>	Slight Odour
<b>Odour threshold</b>	No data available.

<b>Melting point/freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/boiling range</b>	45 °C
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	5.9 % volume [ <i>Details:</i> Tested according to ASTM Method E681-98 (per Annex A1)]
<b>Flammable Limits(UEL)</b>	14.5 % volume [ <i>Details:</i> Tested according to ASTM Method E681-98 (per Annex A1)]
<b>Flash point</b>	No flash point [ <i>Details:</i> Tested according to ASTM Method D3278-96 e-1]
<b>Autoignition temperature</b>	408 °C
<b>Decomposition temperature</b>	<i>Not applicable.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	0.315 mm <sup>2</sup> /sec
<b>Water solubility</b>	Slight (less than 10%)
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Vapour pressure</b>	47,995.9 Pa [ @ 25 °C ]
<b>Density</b>	1.27 g/ml
<b>Relative density</b>	1.27 [ <i>Ref Std:</i> WATER=1]
<b>Relative Vapor Density</b>	2.26 [ @ 25 °C ] [ <i>Ref Std:</i> AIR=1]

### 9.2. Other information

#### 9.2.2 Other safety characteristics

<b>EU Volatile Organic Compounds</b>	1,270 g/l
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>No data available.</i>
<b>Percent volatile</b>	100 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Strong bases.

Strong oxidising agents.



**10.6 Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	At elevated temperatures. - extreme conditions of heat
Carbon dioxide.	At elevated temperatures. - extreme conditions of heat
Hydrogen Chloride	At elevated temperatures. - extreme conditions of heat
Hydrogen Fluoride	At elevated temperatures. - extreme conditions of heat
Perfluoroisobutylene (PFIB).	At elevated temperatures. - extreme conditions of heat
Toxic vapour, gas, particulate.	At elevated temperatures. - extreme conditions of heat

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme conditions of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

<b>SECTION 11: Toxicological information</b>
--

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Contact with the skin during product use is not expected to result in significant irritation.

**Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects: Single exposure may**
**cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation Vapour (4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
trans-dichloroethylene	Dermal	Rabbit	LD50 > 5,000 mg/kg
trans-dichloroethylene	Inhalation Vapour (4 hours)	Rat	LC50 95.6 mg/l
trans-dichloroethylene	Ingestion	Rat	LD50 7,902 mg/kg
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane	Inhalation Vapour (4 hours)	Rat	LC50 > 989 mg/l
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane	Ingestion	Rat	> 2,000 mg/kg
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	Dermal		LD50 estimated to be > 5,000 mg/kg
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	Inhalation Vapour (4 hours)	Rat	LC50 > 1,000 mg/l
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	Ingestion	Rat	LD50 > 5,000 mg/kg

propan-2-ol	Dermal	Rabbit	LD50 12,870 mg/kg
propan-2-ol	Inhalation Vapour (4 hours)	Rat	LC50 72.6 mg/l
propan-2-ol	Ingestion	Rat	LD50 4,710 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
trans-dichloroethylene	Rabbit	Minimal irritation
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Rabbit	No significant irritation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Rabbit	No significant irritation
propan-2-ol	Multiple animal species	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
trans-dichloroethylene	Rabbit	Moderate irritant
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Rabbit	No significant irritation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Rabbit	No significant irritation
propan-2-ol	Rabbit	Severe irritant

**Skin Sensitisation**

Name	Species	Value
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Guinea pig	Not classified
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	Guinea pig	Not classified
propan-2-ol	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
trans-dichloroethylene	In Vitro	Not mutagenic
trans-dichloroethylene	In vivo	Not mutagenic
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	In Vitro	Not mutagenic
Reaction Mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	In vivo	Not mutagenic
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	In Vitro	Not mutagenic
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane	In vivo	Not mutagenic
propan-2-ol	In Vitro	Not mutagenic
propan-2-ol	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
------	-------	---------	-------

propan-2-ol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
-------------	------------	-----	--

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
trans-dichloroethylene	Inhalation	Not classified for development	Rat	NOAEL 24 mg/l	during organogenesis
Reaction Mass of 2-(ethoxydifluoromethyl)1,1,1,2,3,3,3-heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4-nonafluoro-butane	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1methoxybutane	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
propan-2-ol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
propan-2-ol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
trans-dichloroethylene	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
trans-dichloroethylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
trans-dichloroethylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 4,500 mg/kg	not applicable
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluoro-butane	Inhalation	cardiac sensitisation	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluoro-butane	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours

Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	Inhalation	cardiac sensitisation	Not classified	Dog	NOAEL 913 mg/l	10 minutes
propan-2-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propan-2-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
propan-2-ol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
propan-2-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
trans-dichloroethylene	Inhalation	endocrine system   liver   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 16 mg/l	90 days
trans-dichloroethylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
trans-dichloroethylene	Ingestion	blood   liver	Not classified	Rat	NOAEL 125 mg/kg/day	14 weeks
trans-dichloroethylene	Ingestion	heart   immune system   respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system   gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
		eyes   kidney and/or bladder   respiratory system				
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
propan-2-ol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
propan-2-ol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
propan-2-ol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

**Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from Acota assessments.

**12.1. Toxicity**

Material	Organism	Type	Exposure	Test endpoint	Test result
Acota HFE 72DA Engineered Fluid	Water flea	Calculated-Additive Toxicity	48 hours	EC50	>300 mg/l

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
trans-dichloroethylene	156-60-5	Anaerobic sludge	Experimental	96 hours	IC50	48 mg/l
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	425-340-0	Green algae	Analogous Compound	72 hours	EC10	2.37 mg/l
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	425-340-0	Green algae	Experimental	72 hours	EC10	2.37 mg/l
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	422-270-2	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1methoxybutane	422-270-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
trans-dichloroethylene	156-60-5	Experimental Photolysis		Photolytic half-life (in air)	13 days (t 1/2)	
trans-dichloroethylene	156-60-5	Experimental Biodegradation	28 days	Percent degraded	8 % BOD/ThB OD	OECD 301D - Closed bottle test
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	425-340-0	Estimated Photolysis		Photolytic half-life (in air)	0.55 years (t 1/2)	Non-standard method
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	425-340-0	Estimated Biodegradation	28 days	BOD	0 % BOD/ThB OD	OECD 301D - Closed bottle test
Reaction Mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3heptafluoropropane and 1ethoxy-1,1,2,2,3,3,4,4,4nonafluorobutane	425-340-0	Analogous Compound Biodegradation	28 days	BOD	0 % BOD/ThB OD	OECD 301D - Closed bottle test

Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1-methoxybutane	422-270-2	Experimental Photolysis		Photolytic half-life (in air)	2.9 years (t 1/2)	Non-standard method
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1-methoxybutane	422-270-2	Experimental Biodegradation	28 days	BOD	22 % BOD/ThB OD	OECD 301D - Closed bottle test
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1-methoxybutane	422-270-2	Analogous Compound Biodegradation	28 days	BOD	22 % BOD/ThB OD	OECD 301D - Closed bottle test
propan-2-ol	67-63-0	Experimental Biodegradation	14 days	BOD	86 % BOD/ThB OD	OECD 301C - MITI test (I)

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
trans-dichloroethylene	156-60-5	Experimental Bioconcentration		Log Kow	2.06	
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1-methoxybutane	422-270-2	Experimental Bioconcentration		Log Kow	4.0	Non-standard method
Reaction Mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4nonafluoro-1-methoxybutane	422-270-2	Analogous Compound Bioconcentration		Log Kow	4.0	
propan-2-ol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	Non-standard method

**12.4. Mobility in soil**

Material	Cas No.	Test type	Study Type	Test result	Protocol
trans-dichloroethylene	156-60-5	Estimated Mobility in Soil	Koc	61 l/kg	Episuite™

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects **12.7.**

**Other adverse effects**

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
reaction mass of 2(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4nonafluoro-butane	425-340-0	0	



**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of Acota, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

070103\*      Organic halogenated solvents, washing liquids and mother liquors

**SECTION 14: Transportation information**

Not hazardous for transportation.

	<b>Ground Transport (ADR)</b>	<b>Air Transport (IATA)</b>	<b>Marine Transport (IMDG)</b>
<b>14.1 UN number or ID number</b>	No data available.	No data available.	No data available.
<b>14.2 UN proper shipping name</b>	No data available.	No data available.	No data available.
<b>14.3 Transport hazard class(es)</b>	No data available.	No data available.	No data available.
<b>14.4 Packing group</b>	No data available.	No data available.	No data available.
<b>14.5 Environmental hazards</b>	No data available.	No data available.	No data available.
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.

<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	No data available.	No data available.	No data available.
<b>IMDG Segregation Code</b>	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact Acota for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
trans-dichloroethylene	156-60-5	10	50
propan-2-ol	67-63-0	10	50

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

#### List of relevant H statements

EUH018	In use, may form flammable/explosive vapour-air mixture.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

- H412 Harmful to aquatic life with long lasting effects.  
H413 May cause long lasting harmful effects to aquatic life.

### Revision information:

EU Section 09: pH information information was added.  
Industrial Laboratory Use: Section 16: Annex information was modified.  
Industrial Use as a Solvent: Section 16: Annex information was modified.  
Industrial Use in Vapour Degreasing Systems: Section 16: Annex information was modified.  
Industrial Use of Cleaners: Section 16: Annex information was modified.  
Laboratory Use: Section 16: Annex information was modified.  
Professional Laboratory Use: Section 16: Annex information was modified.  
Professional Use as a Solvent: Section 16: Annex information was modified.  
Section 1: Product identification numbers information was modified.  
Section 01: SAP Material Numbers information was modified.  
Label: CLP Precautionary - Disposal information was deleted.  
Label: CLP Supplemental Precautionary Statements information was deleted.  
Section 02: SDS Elements: CLP Supplemental Precautionary Statements information was added.  
Section 03: Composition table % Column heading information was added.  
Section 3: Composition/ Information of ingredients table information was modified.  
Section 03: Substance not applicable information was added.  
Section 04: First Aid - Symptoms and Effects (CLP) information was added.  
Section 04: Information on toxicological effects information was modified.  
Section 5: Fire - Advice for fire fighters information information was modified.  
Section 5: Fire - Special hazards information information was modified.  
Section 6: Accidental release clean-up information information was modified.  
Section 6: Accidental release personal information information was modified.  
Section 7: Precautions safe handling information information was modified.  
Section 8: Appropriate Engineering controls information information was modified. Section 8: Occupational exposure limit table information was modified.  
Section 8: Personal Protection - Respiratory Information information was modified.  
Section 8: Personal Protection - Skin/hand information information was modified.  
Section 8: Personal Protection - Thermal hazards information information was deleted.  
Section 9: Evaporation Rate information information was deleted.  
Section 9: Explosive properties information information was deleted.  
Section 09: Kinematic Viscosity information information was added.  
Section 9: Melting point information information was modified.  
Section 9: Oxidising properties information information was deleted.  
Section 9: pH information information was deleted.  
Section 9: Property description for optional properties information was modified.  
Section 9: Vapour density value information was added.  
Section 9: Vapour density value information was deleted.  
Section 9: Viscosity information information was deleted.  
Section 11: Classification disclaimer information was modified.  
Section 11: No endocrine disruptor information available warning information was added.  
Section 11: Reproductive Toxicity Table information was modified.  
Section 11: Target Organs - Repeated Table information was added.  
Section 11: Target Organs - Repeated Table information was deleted.  
Section 12: 12.6. Endocrine Disrupting Properties information was added.  
Section 12: 12.7. Other adverse effects information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Section 12: Contact manufacturer for more detail. information was deleted.  
Section 12: Mobility in soil information information was added.  
Section 12: No endocrine disruptor information available warning information was added.  
Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.  
 Section 14 Classification Code – Main Heading information was added.  
 Section 14 Classification Code – Regulation Data information was added.  
 Section 14 Control Temperature – Main Heading information was added.  
 Section 14 Control Temperature – Regulation Data information was added.  
 Section 14 Disclaimer Information information was added.  
 Section 14 Emergency Temperature – Main Heading information was added.  
 Section 14 Emergency Temperature – Regulation Data information was added.  
 Section 14 Hazard Class + Sub Risk – Main Heading information was added.  
 Section 14 Hazard Class + Sub Risk – Regulation Data information was added.  
 Section 14 Hazardous/Not Hazardous for Transportation information was added.  
 Section 14 Other Dangerous Goods – Main Heading information was added.  
 Section 14 Other Dangerous Goods – Regulation Data information was added.  
 Section 14 Packing Group – Main Heading information was added.  
 Section 14 Packing Group – Regulation Data information was added.  
 Section 14 Proper Shipping Name information was added.  
 Section 14 Regulations – Main Headings information was added.  
 Section 14 Segregation – Regulation Data information was added.  
 Section 14 Segregation Code – Main Heading information was added.  
 Section 14 Special Precautions – Main Heading information was added.  
 Section 14 Special Precautions – Regulation Data information was added.  
 Section 14 Transport in bulk – Regulation Data information was added.  
 Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was added.  
 Section 14 UN Number Column data information was added.  
 Section 14 UN Number information was added.  
 Section 15: Regulations - Inventories information was added.  
 Section 15: Seveso Substance Text information was added.  
 Section 2: No PBT/vPvB information available warning information was added.

### Annex

<b>1. Title</b>	
<b>Substance identification</b>	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
<b>Exposure Scenario Name</b>	Industrial Laboratory Use
<b>Lifecycle Stage</b>	Widespread use by professional workers
<b>Contributing activities</b>	PROC 15 -Use a laboratory reagent ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
<b>Processes, tasks and activities covered</b>	Use as a laboratory reagent.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use; Indoors with LEV and good general ventilation;

<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.
<b>1. Title</b>	
<b>Substance identification</b>	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
<b>Exposure Scenario Name</b>	Industrial Use as a Solvent
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 07 -Industrial spraying PROC 08a -Transfer of substance or mixture (charging and discharging) at nondedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities

	PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 07 -Use of functional fluid at industrial site
<b>Processes, tasks and activities covered</b>	Cleaning process equipment and parts. Cleaning surfaces by wiping, brushing. Spraying of substances/mixtures. Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Discharge volume of sewage treatment plant: 2,000,000 liters per day; Emission days per year: 365 days per year; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoors with enhanced general ventilation; Indoors with good general ventilation; Large factory building (> 500 m <sup>3</sup> ); Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;  <b>Task: Spraying;</b> Duration of use: 4 hours/day;  <b>Task: Transferring Material;</b> Duration of use: 4 hours/day;  <b>Task: Wiping Surfaces;</b> Duration of use: 4 hours/day;

<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.
<b>1. Title</b>	
<b>Substance identification</b>	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
<b>Exposure Scenario Name</b>	Industrial Use in Vapour Degreasing Systems
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 04 -Chemical production where opportunity for exposure arises PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 07 -Use of functional fluid at industrial site
<b>Processes, tasks and activities covered</b>	Draining process equipment. Transfer of substance/mixture with dedicated engineering controls. Vapour Degreasing
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Discharge volume of sewage treatment plant: 2,000,000 liters per day; Duration of use: 8 hours/day; Emission days per year: 300 days per year; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoor use without Local Exhaust Ventilation; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; Medium sized room or workshop ( 100 m <sup>3</sup> - 500 m <sup>3</sup> ); Partially open and partially closed process;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Incinerate in a facility capable of handling halogenated waste;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	propan-2-ol; EC No. 200-661-7; CAS Nbr 67-63-0;
<b>Exposure Scenario Name</b>	Industrial Use of Cleaners
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 04 -Chemical production where opportunity for exposure arises PROC 07 -Industrial spraying PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Application of product with a roller or brush. Spraying of substances/mixtures. Transfers with dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of use: 8 hours/day;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and
	PNECs when the identified risk management measures are adopted.
<b>1. Title</b>	
<b>Substance identification</b>	propan-2-ol; EC No. 200-661-7; CAS Nbr 67-63-0;
<b>Exposure Scenario Name</b>	Laboratory Use
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 15 -Use a laboratory reagent ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Use as a laboratory reagent.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 4 hours/day;

<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.
<b>1. Title</b>	
<b>Substance identification</b>	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
<b>Exposure Scenario Name</b>	Professional Laboratory Use
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 15 -Use a laboratory reagent ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Use as a laboratory reagent.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Discharge volume of sewage treatment plant: 2,000,000 liters per day; Duration of use: 8 hours/day; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoors with LEV and good general ventilation; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Incinerate in a facility capable of handling halogenated waste;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.
<b>1. Title</b>	
<b>Substance identification</b>	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
<b>Exposure Scenario Name</b>	Professional Use as a Solvent
<b>Lifecycle Stage</b>	Widespread use by professional workers



<b>Contributing activities</b>	<p>PROC 08a -Transfer of substance or mixture (charging and discharging) at nondedicated facilities</p> <p>PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities</p> <p>PROC 10 -Roller application or brushing</p> <p>PROC 11 -Non industrial spraying</p> <p>PROC 13 -Treatment of articles by dipping and pouring</p> <p>ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)</p> <p>ERC 09a -Widespread use of functional fluid (indoor)</p>
<b>Processes, tasks and activities covered</b>	<p>Cleaning process equipment and parts. Cleaning surfaces by wiping, brushing. Spraying of substances/mixtures. Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.</p>
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<p><b>Physical state:</b>Liquid. <b>General operating conditions:</b> Indoors with good general ventilation; Medium sized room or workshop ( 100 m<sup>3</sup> - 500 m<sup>3</sup>);</p> <p><b>Task: Pouring Material - Liquids;</b> Duration of use: 15 min - 1 hour task;</p> <p><b>Task: Spraying;</b> Duration of use: 15 min - 1 hour task;</p> <p><b>Task: Wiping Surfaces;</b> Duration of use: 15 min - 1 hour task;</p>
<b>Risk management measures</b>	<p>Under the operational conditions described above the following risk management measures apply:</p> <p><b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;</p>
<b>Waste management measures</b>	<p>No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:</p>
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	<p>Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.</p>

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.